

# **Pharmacy Refrigerator**

# FSF-5V60G

Pharmacy refrigerators are specially designed to store medicines, vaccines, regents and biomedical products.



#### **Features**

- Adjustable temperature range 2-8℃
- Microprocessor control, digital display, and temperature adjustment with an increment of 0.1°C
  Large digital display screen
- Temperature variation within ±3℃
- Permanently lubricated cooling fan for safety and longevity
- High efficiency specialty compressor with known field reliability
- Forced- air cooling with optimized air distribution system designed

### **Safety**

- Build-in back-up battery to display temperature and to operate audible and visual alarm system for up to 8 hours without AC power.
- Visual and audible alarm system: High/low temperature, thermostat failure alarm, power failure alarm, door ajar.
- Power failure protection: turn on delay of the cooling system when power failure,restart delay protection.
- Keyboard lock, password protection to avoid set parameter randomly.
- Wide available voltage range: 187V~242V.

## **Humanized design**

- Optimized space utilization design with multi level and adjustable shelf height to accommodate storage requirement of pharmaceutical products of various kinds.
- Standard with LED Interior light
- Safety lock to prevent unauthorized access

Performance		
Temperature Range	+2~+8℃	
Ambient Temperature	10~32°C	
Controller	Microprocessor	
Display	Digital Display	
Electrical Data		
Power Supply(V/Hz)	220/50~60; 115/60	
Rated Power(W)	72	
Electrical Current(A)	0.59	
Power Consumption	0.84 kWh/24h	
Dimensions		
Capacity	60L	
Interior Size(W*D*H)	410*315*560m	
Exterior Size(W*D*H)	495*450*710m	
Package Size(W*D*H)	558*510*760m	
N.t./G.t.(approx)	33/37kg	
Loading Qty(20'/40'/40'H)	132/276/276	

Refrigeration System	
Compressor	1
Refrigerant	R600a
Cooling Type	Forced-air cooling
Defrost Type	Frost free
Alarm	
High/Low Temperature	Y
Power Failure	Y
Door ajar	Y
Thermostat failure	Υ
Accessories	
Caster	/
Lamp	LED
Door	1(Glass door)
Shelf	2
Test hole	1/25mm
Temperature recorder	Optional